



IMPERIAL

BRICK TILES

AUTHENTIC FEATURE WALLS

FEATURE WALL WOOD PANELS INSTALLATION GUIDE

Create tactile statement interiors with the Feature Wall Wood Panel collection



Interior walls and other surfaces can be transformed quickly and easily with our innovative three dimensional interlocking, pre-sealed wooden wall panels. Offering a charming, rustic reclaimed timber finish, our Feature Wall Wood Panels will create superlative interiors with a warm ambience.

Individual pieces of timber are randomly selected and bonded onto a backing material for ease of application. This production process results in natural colour variation within each panel.

Made from FSC certified sustainable wood sources and perfectly engineered with an interlocking design to fit together seamlessly, these on trend wall panels are available in a range of attractive colours which bring the natural beauty and texture of real wood into an easy to install format.

Suitable for indoor applications, Feature Wall Wood Panels are light and durable, supplied in boxed packaging, and incredibly easy to install for professional or DIY installation, following these simple step-by-step instructions.

You will need:

- ✓ A square
- ✓ Small electric saw
- ✓ Sander
- ✓ Recommended adhesive such as instant grab silicone (for use in glass, windows, ceramics etc) or MS adhesive.



SEVEN SIMPLE STEPS

1. Open the boxes for 24 hours before installation to let the Feature Wall Wood Panels adapt to the temperature and humidity where they will be installed.
2. Calculate the surface area to be covered.
3. Remove any loose paint or plaster and repair any flaking surfaces. Dust down the prepared surface and remove any grease or dirt.
4. Apply the recommended adhesive to the back of the panel's surface evenly.
5. Offer the first panel up to the fitting surface and confirm it is square and level, then press it firmly for 5 seconds to ensure the entire panel is flat against the surface. This is necessary to avoid any bulging. A headless panel pin can also be used if the wall is slightly uneven.
6. To fit the next panel, make sure that its position is aligned with the previous one using the interlocking design.
7. If panels need to be cut down to size, simply tear along a glued joint, then use a saw to cut the wood to the required size. Any rough edges can be smoothed with a sander if desired.

IMPORTANT: If using nails or pins to fix the panels, you must ensure there are no hidden pipes or electric cables/fittings.

Maintenance & Cleaning

Panels are easy to maintain. They can be wiped with a damp cloth, or using a neutral detergent diluted with water.

Storage

The product should be stored in a horizontal position, stacked to a maximum of ten boxes. Must be stored in a dry environment, preferably on a pallet.

Note: Our Feature Wall Wood Panels are 100% natural and are made using a manual production process. Each panel is unique and offers characteristic variations in colour and patina, which is part of the natural charm of this mosaic.

All adhesives, sealants and grouts must be used in accordance with manufacturer guidelines.